

Experimental Study of Debris-Induced Scour around a Slotted Bridge Pier

Hossein Hamidifar^{1,*}, Damoon Mohammad Ali Nezhadian², Iacopo Carnacina³

¹Water Engineering Department, Shiraz University, Shiraz, Iran. <https://orcid.org/0000-0001-9054-0120>

²Water Engineering Department, Shiraz University, Shiraz, Iran. <https://orcid.org/0000-0003-2909-8032>

³ School of Civil Engineering and Built Environment, Liverpool John Moores University, Peter Jost Centre, Byrom Street, Liverpool L3 3AF, UK. <https://orcid.org/0000-0001-5567-7180>

*Corresponding author's e-mail: hamidifar@shirazu.ac.ir

Declarations

Funding: No funding was received for conducting this study.

Conflicts of interest/Competing interests: The authors declare that they have no known competing interests.

Availability of data and material: All data generated or used during the study appear in the submitted article.

Code availability: No code was generated for conducting this study.

Ethics approval: Not applicable.

Consent to participate: Not applicable.

Consent for publication: Not applicable.

Experimental Study of Debris-Induced Scour around a Slotted Bridge Pier

Abstract

One of the most common problems for river engineers is the accumulation of waterborne debris upstream of the bridge piers. In addition to reducing the cross-sectional flow area, debris increases the drag force exerted to the pier and contributes to scour. Several studies have been carried out by previous researchers to examine the usefulness of different types of countermeasures. The effectiveness of these countermeasures is not well understood when debris accumulation occurs. In this study, the effect of debris accumulation on the efficiency of a bridge pier slot, as scour countermeasure, is investigated experimentally. A total of 54 experiments were carried out under different hydraulic and debris geometrical conditions. The results showed that slots were effective in protecting bridge piers against scouring in presence of debris. Depending on the debris shape, the reduction efficiency may increase or decrease for a slotted pier in presence of debris accumulation when compared to the standard pier conditions without debris accumulation. Except for the inverse pyramid shape, the maximum scour is generally more reduced due to sheltering effect when the debris is located on the bed. While debris accumulation can lead to a reduction of the slot efficiency, the slot can be considered a reliable countermeasure against scouring. The outcome of this study can help the design of new bridges affected by large wood debris accumulations.

Keywords: bridge pier, scour, debris accumulation, slot, structural failure.

Introduction

Bridges play an important role in public transportation and their damage causes significant economic losses and significant disruption to communities. One of the most important factors in dynamic behavior, fragility, and bridge structural collapse is bed scouring around the pier and the consequent failure of the foundation [1–5]. Estimating scour depth around bridge piers has been thoroughly studied by many researchers in the past [6–9]. Despite the efforts made so far, sufficient understanding of the mechanism of local scouring around bridge piers has not yet been achieved, and every year many bridges around the world are damaged, which causes severe human and financial losses. In general, two methods have been proposed to protect bridge piers against bed scouring: increasing the bed material strength, and modifying the flow pattern around the pier. In the first method, the resistance of bed particles movement caused by flow shear is increased using materials with a larger sediment transport threshold velocity, e.g., riprap [10–15], geo-bags [16, 17], gabions [18, 19], or tetrahedral frames [20]. In the second method, the flow pattern and the turbulent structure normally observed around piers, i.e., the downflow, horseshoe vortex and wake, which are the main cause of the local erosion of the bed material, is drastically modified by making changes to the pier or in its vicinity. In particular, scouring is reduced or eliminated by reducing the strength of the erosive flow. Collars [21–26], threadings [27, 28], bed-sills [18, 29–32], vanes [33, 34], splitter plates [35], sacrificial piles [36, 37], and slots [24, 38–45] are some example of the methods that have been proposed to reduce scouring around bridge piers by modifying the flow pattern.

Slot protections have shown promising results. A slot is an opening in the pier that causes a portion of the flow to pass through the pier. It has been found that the downflow and the wake vortex system is weakened due to the presence of the slot [38, 46]. The use of slots in bridge piers was first reported by Tanaka and Yano (1967) as a new method in controlling scouring around the

71 pier. They found that a slot can reduce the maximum scour depth by up to 30% compared to the
72 standard piers. Chiew (1992) investigated the effect of slots on scour around a cylindrical pier and
73 concluded that using a slot with a width equal to 1/4 of the pier diameter reduces the maximum
74 scour depth by 20%. Also, the results of an experimental study conducted by Kumar et al. (1999)
75 indicated an 18% and 33% reduction in the maximum scour depth for a slot located above the
76 initial bed and a slot extended beneath the bed, respectively. Tafarjnoruz et al. (2012) examined
77 the effectiveness of six different methods for pier protection against scouring. They concluded that
78 slot, collar, or sacrificial piles are up to 15% more effective in reducing scouring compared to
79 threading, submerged vanes, and a bed-sill. Azevedo et al. (2014) evaluated the use of a slot in
80 reducing the maximum scour depth around circular and elongated bridge piers and observed a
81 reduction of the maximum scour depth up to 26% and 16% for the circular and elongated pier,
82 respectively. Also, Hosseini et al. (2020) and Osrush et al. (2019) conducted experimental studies
83 on the effects of the size and vertical position of slots on the reduction of scouring around
84 rectangular abutments. They concluded that slots are more effective in abutments than bridge piers
85 against scouring. In a more recent study, Bestawy et al. (2020) studied different types of pier slots
86 geometries, showing that the sigma-shaped slots performed better than other geometries tested.

87 Several studies show that a better result is obtained if a combination of a slot and other
88 scour countermeasures are used around the pier. For example, Chiew (1992) observed that the
89 collar-slot combination is more effective in reducing scour depth than either the collar or the slot
90 alone. Grimaldi et al. (2009b) studied the effect of combining a slot with bed-sill on scouring
91 around the pier. They concluded that this method could reduce the maximum scouring depth up to
92 45% and could therefore be used as an effective method of controlling scouring around the pier.
93 Also, Gaudio et al. (2012) examined five different combinations of scour reduction methods

around the pier and concluded that the combination of slot and bed-sill has been more effective compared to the other four combinations tested. It has been proven that the scouring depth decreases with increasing the length of the slot, and if the slot is used in combination with a collar, almost no scouring will occur around the pier [50].

The mobility and accumulation of floating debris at bridge piers is a growing problem around the world [51–55]. Floating debris also called large woody debris (LWD) [56] or driftwood [57, 58], refers to the fragments of tree trunks, branches, eroded materials, which are mainly found in areas where trees are growing near the river banks [59, 60]. Many studies indicate that the accumulation of such floating objects upstream of the pier leads to an increase in the effective width of the pier, increase the shear stress, change the flow pattern, turbulence, and, consequently, the scouring mechanism, increasing the risk of bridge failure [18, 59, 69–71, 61–68].

While Briaud et al. (2006) reported that about 10% of all bridges constructed over waterways in the USA are exposed to additional scouring due to debris accumulation, Diehl (1997) estimated the incidence of debris to bridge failure as one in three cases for the US, and Benn (2013) produced similar figures for UK and Ireland. Also, heavier debris accumulation occurs in single piers [73]. Ebrahimi et al. (2018) reported that cylindrical debris located beneath the water surface increases the maximum scour depth up to 33% compared to no-debris case. Another study by Pagliara et al. (2010) revealed that the maximum scour depth around the bridge pier with debris accumulation can be increased up to three times that without debris accumulation. Also, Park et al. (2016) observed that due to debris accumulation upstream of a single pier, the maximum scour depth increased up to 60% compared to no-debris conditions. Also, Pagliara and Carnacina (2011) experimentally studied the effect of debris accumulation on bridge pier scour. They used three wood debris shapes including triangular, cylindrical, and rectangular with various thicknesses and

widths. They related the scour depth around the bridge pier to the blockage ratio due to debris accumulation. Additional studies by [37, 70, 71, 75] showed that the location and shape of debris accumulation has a considerable impact on the final scour depth.

Several mitigation measures have been developed in the past to reduce debris accumulating at bridge structures, for example, Schmocker and Weitbrecht (2013) tested a bypass system, Panici and Kripakaran (2021) a series of inclined racks, and Franzetti et al. (2011) examined wedges upstream of a pier to keep debris away. However, the efficiency of some scour countermeasures, for example, bed-sills, gabions, and sacrificial piles have been found to decrease due to debris accumulation [18, 37, 71, 76]. Although the studies done so far on scouring reduction have shown the effective role of slots, there are still gaps in its utilization in practice. For example, slots may be fully or partially clogged by the accumulation of debris carried by flood currents [38]. Despite advances in scouring around bridge piers so far, the effect of debris accumulation upstream of the slotted bridge piers is still a concern for designers and engineers due to insufficient information. The main purpose of the present study is to investigate experimentally the effect of the accumulation of debris upstream of single circular cylindrical bridge piers with and without a slot. Also, the effect of the shape of the debris accumulated upstream of the pier as well as the flow characteristics on the scour hole around the pier has been investigated. Finally, the effect of the debris position (near the water surface or in the vicinity of the channel bed) on the scouring and the slot efficiency has been analyzed.

Materials and Methods

The experimental tests were carried out at the Sediment Hydraulics Laboratory of Shiraz University, Shiraz, Iran under clear-water flow conditions. A glass-walled rectangular recirculating flume with 0.4 m width, 9 m length and a bed slope of 0.002 was used for the experiments (Figure 1a). A series of 0.5m long PVC pipes with 20mm diameter was used as a flow straightener to reduce disturbances of the entrance flow as shown in Figure 1a. The 0.2 m deep alluvial bed was composed of uniform sediments with a median particle diameter (d_{50}) of 0.8 mm, a geometric standard deviation ($\sigma_g = \sqrt{d_{84}/d_{16}}$) of 1.3, and specific gravity (S_g) of 2.65, where d_{50} , d_{84} , and d_{16} are the particle sizes for which 50, 84, and 16% of sediment grains are finer. The bridge pier was modeled based on the criteria suggested by Chiew and Melville (1987). Accordingly, the effect of the pier width on the scouring is negligible when the pier width is less than 10% of the flume width. Also, the ratio of the pier width to median particle diameter (D/d_{50}) must be greater than 30 to ensure that the sediment size does not affect the rate of scouring [78]. A fiberglass cylinder with 0.5 m height and a diameter of $D=40\text{mm}$ was used in the experiments. A slot with a height equal to the flow depth ($h=H$) and width of $b=10\text{ mm}$ ($b=0.25D$) was made in the center of the pier model based on Chiew (1992), who recommended the width of 1/4 of the pier diameter as the optimal slot width. The shape of woody debris observed in the literature ranges from a simple cylindrical log [61, 74, 79] to more complex shapes such as rectangular debris [63, 64] and inverted triangular or conical shapes [54, 63, 64, 74, 80] and it is influenced by flow conditions, channel geometry, pier shape, and woody debris characteristics and availability. In this study, two circular cylinders of 12- and 24-mm diameters, an inverse pyramid, and a rectangular plate made of fiberglass were transversally attached to the upstream side of the pier (Fig. 1b) to simulate single logs, debris jam protruding vertically upstream of the pier, and a woody debris accumulation at

the water surface. As the main purpose of the present study is to investigate the slot performance in scour depth mitigation in the presence of debris, the shape of the debris is of secondary importance here. The top of the debris was tangent to the water surface. Also, in some tests, the debris was located on the channel bed to study the effect of debris position on the scour process (Fig. 1c). The ratio of the modeled debris length in the vertical direction (L_z) to that in the transverse direction (L_y), i.e. L_z/L_y , was in the range of 0.06-0.12, which is close to the range observed by Ebrahimi et al. (2018). This range is close to the average ratio reported by several researchers in field conditions [59, 81–84]. Three different flow discharges of 12.9, 15.3, and 16.7 l/s producing flow depths of 0.13, 0.16, and 0.18 m, respectively, were used in the experiments. The flow depth for each discharge mentioned above was calculated based on the flow intensity, i.e. U/U_c , of 0.83, 0.77, and 0.73, respectively, where U is the cross-sectional averaged flow velocity and U_c is the critical flow velocity for the incipient motion of the sediment particles according to the Shields diagram. While the maximum scour depth occurs for U/U_c (almost) equal to 1, there may be several cases in the field conditions where the flow intensity is much lower than 1 [85]. Although flows with $U/U_c < 1$ may not lead to the maximum scouring, the presence of debris can significantly alter the scouring depth and it is important to understand the impact of debris accumulation also at lower flow intensities, as experimented in several other works [63, 64, 74]. The flow depth was adjusted using a tailgate located at the downstream end of the laboratory flume. At the end of each experiment, the flume was drained, the debris was removed and the topography of the scoured bed was measured using an optical meter with a precision of ± 0.1 mm mounted on a carriage. The carriage was able to move in the streamwise as well as the transverse directions in a 20 mm \times 20 mm grid to give a 3-D view of the scoured bed. A summary of the experimental conditions and debris dimensions are given in Table 1.

Fig. 1. a) schematic view of the experimental flume (Not to scale), b) slot and debris position, c) a photo of the pier and debris located on the bed, and d) different debris types used in the experiments

Table 1. Summary of the experimental conditions

Each test was continued until reaching a quasi-equilibrium condition based on the criteria suggested by Chiew and Melville (1987) who reported that the equilibrium scouring depth can be considered when the variations in the scour depth is less than 5% of the pier diameter during 24 hours. A series of 48-hours long tests showed that the quasi-equilibrium conditions were met after 6 hours, and this was the final duration selected for all the experimental runs. Each test is identified by a combination of letters and numbers. Thereafter, NS and ND, refer to the tests without slot and debris, respectively, S stands for the tests with slot, and D1, D2, D3, and D4 refers to cylindrical debris of 12mm diameter, cylindrical debris of 24-mm diameter, inverse pyramid, and rectangular debris shapes, respectively. The last part in each test name indicates the approach flow Froude number, where $Fr_1=0.220$, $Fr_2=0.191$, and $Fr_3=0.175$, respectively. The parameters affecting the scouring around a cylindrical bridge pier with impervious debris accumulations in a fluvial bed with uniform sediments are: the flow depth (h), mean flow velocity (V), bed slope (S), channel width (B), bed roughness (k_s), water (ρ_w) and bed particles (ρ_s) specific mass, acceleration due to gravity (g), viscosity (ν), pier diameter (D), particle size (d_{50}), debris dimensions in the streamwise, transverse, and vertical directions (L_x , L_y , and L_z respectively), debris specific mass (ρ_d), debris frontal area (A_d), debris distance to the water surface (h_d). By excluding the parameters that were kept constant in the present study, i.e., h/D , S , B/D , k_s/D , ρ_s/ρ_w , d_{50}/D , and ρ_d/D , and neglecting the effect of Reynolds number $Re=\rho_w Vh/\nu$ because of the turbulent flow conditions, the non-

dimensional maximum scour depth d_{sm}/D was found to be a function of Froude number $Fr=V/\sqrt{(g.h)}$, and the debris geometrical parameters L_x/D , L_z/D , h_d/D , and A_d/D^2 .

Results

The first part of the results section provides a qualitative description of the effect of debris accumulation, the presence of a slot, and their combinations. In the second part, these findings are quantitatively elaborated. Figure 2 shows variations of the non-dimensional maximum scour depth around the pier, d_{sm}/D , for different flow and debris conditions for $Fr_1=0.22$. The slot reduces the maximum scour depth compared to the standard pier under both no-debris and debris conditions. These findings are comparable to those of previous studies on standard piers without debris (for example Chiew, 1992; Grimaldi et al., 2009b; M Heidarpour, 2002; Kumar et al., 1999; Moncada-M et al., 2009).

Figure 3 shows variations of d_{sm}/D against Fr and for different debris conditions. The maximum scour depth decreases due to the presence of the slot in the pier for a given debris condition and the maximum scouring depth decreases as the Froude number decreases. However, the maximum scouring depth increases compared to the no-debris conditions for all the tests with different shapes of debris placed right beneath the water surface. The maximum scouring depth increases as the debris diameter increases for the cylindrical shape debris placed near the water surface. This trend is completely reversed for a debris placed on the channel bed.

The figure also shows how the maximum scouring depth increases compared to the tests with debris located near the water surface as well as the tests with no-debris conditions in the cases of an inverse pyramid debris located above the channel bed.

Additionally, for all the slotted and standard piers tests with rectangular debris, the near-bed accumulation of debris has reduced the maximum scour depth compared to the near water surface accumulation of debris material. More explanations and insights on the local scour physics to corroborate these experimental observations are provided in the following discussion.

Fig. 2. Variations of the dimensionless maximum scour depth for slotted and non-slotted piers and different debris conditions ($Fr=0.22$)

Fig. 3. Variations of the dimensionless maximum scour depth (d_{sm}/D) against Froude number (Fr) in different tests: a) ND, b) D1, c) D2, d) D3, e) D4, f) D1-Bed, g) D2-Bed, h) D3-Bed, and i) D4-Bed.

Discussion

To quantify the effect of the presence of slot and debris and its location on the maximum scour depth, the percentage of variation in the d_{sm} relative to the control test (no-debris and no-slot), R_{NS-ND} , is calculated for different tests and shown in Figure 4 for the three flow Froude number tested. R_{NS-ND} is computed as:

$$R_{NS-ND} = \frac{d_{sm} - d_{NS-ND}}{d_{NS-ND}} \times 100 \quad (1)$$

where d_{sm} and d_{NS-ND} denote the maximum scour depth around the pier in each test and the control test (no-slot and no-debris conditions), respectively.

Fig. 4. Variations of the maximum scour depth in the slotted or debris loaded piers compared to that of the control test

For the standard pier tests (no-slot conditions denoted with NS), it can be seen that the maximum scour depth has increased up to 32, 57, 52, and 57%, for debris types D1, D2, D3, and D2, respectively, located under the free water surface. For under-free-water-surface debris, both streamwise and downward components of the flow velocity as well as the bed shear stress increase and consequently increase the maximum scouring depth around the pier. Ebrahimi et al. (2018) also reported similar findings for sharp-nose piers. Figure 3 also shows that the maximum scouring depths for the tests with debris type D2 are greater than the corresponding tests with debris type D1. The reason can be attributed to the fact that debris type D2 produces larger blockage in the flow cross-sectional area and consequently, the flow velocity and bed shear stress will be higher than those of corresponding D1 tests.

The sheltering effect of a debris located near the bed reduces the maximum scour depth by 33%, 44%, and 35% for debris types D1, D2, and D4, respectively, for the standard pier tests, whilst the maximum scour depth increases up to 77% for the debris type D3. The different trend for the inverse pyramid debris shape may be attributed to the re-direction of the near-bed streamlines after impinging the debris (Figure 5). The downward slope of the inverse pyramid causes the flow to redirect toward the bed, as shown in Figure 4, increasing the maximum scouring depth compared to the cases without debris. The sheltering effect of the debris D3 has been neutralized because of the flow redirection and the maximum scour depths in the NS-D3-Bed tests are highest among all the tested conditions.

Figure 4 shows that the slot alone leads to a 37-39% reduction in the maximum scour depth compared to standard pier conditions. However, due to the effects of the debris located near the water surface, the slot efficiency in reducing the maximum scour depth reduces up to 32% and

27% for the D1 and D2 cylindrical debris shapes, respectively. It is interesting to note that when the debris is located near the channel bed, the percentage reduction in the maximum scour depth increases up to 33 and 44% for D1 and D2 cylindrical debris shapes, respectively. Figure 4 shows that the larger the cylindrical shape debris diameter located on the initial bed surface, the smaller the maximum scour depth. The reason may be attributed to the sheltering effect of debris located on the bed. When the debris is located in the vicinity of the bed, the maximum scouring depth around simple bridge piers is mitigated due to the reduced strength of the downflow [71, 74, 86].

Figure 4 also shows that the flow Froude number, in the range tested in the present study, has limited influence on the maximum scour values for the slotted pier without debris and with debris located near the water surface. However, for the standard pier and all of the debris shapes located near the water surface, the Froude number considerably affect the maximum scour depth. In this case, the difference between the R_{NS-ND} values corresponding to the lowest and highest Froude number studied was found to be about 35% for D2 and D3 debris types.

It is interesting to note that the maximum scour may be increased or decreased compared to the standard pier without debris conditions depending on the shape of the debris for the tests with debris located near the bed surface. On the other hand, while D1, D2, and D4 debris types cause the maximum scouring depth to be reduced up to 33%, 43%, and 35%, respectively, the maximum scour depth increases up to 82% for the inverse pyramid debris type (D3). The sheltering effects of the debris causes a considerable reduction in the maximum scouring depth for slotted piers when compared to the standard pier conditions. Additionally, the percentage reduction in the maximum scour depth is not affected by the flow Froude number for the slotted pier with D1 and debris types D2 located on the bed (Fig. 4) in the range of Fr values tested in the present study. The inverse pyramid debris (D3) accumulated on a slotted pier shows a different trend where the

scour depth increases 23% and decreases by 17% for the tests with the highest and lowest Froude numbers studied, respectively, which could be linked to the the reduction in the near-bed flow velocity with decreasing Froude number and the weaker flow field around the slotted pier.

The percentage reduction in the maximum scouring depth increases with decreasing Fr for the debris type D4, which can be attributed to the sheltering effect of these particular configuration of debris.

Fig. 5. Schematic view of flow around different debris types at different positions: a) cylindrical, b) inverse pyramid, c) rectangular debris located just below the free water surface, d) cylindrical, e) inverse pyramid, and f) rectangular debris located above the bed

Fig. 6. Variations of the dimensionless scour depth against dimensionless debris area for the tests with debris located near the water surface, non-slotted pier: a) $Fr=0.22$, b) $Fr=0.19$, and c) $Fr=0.17$, and slotted pier: d) $Fr=0.22$, e) $Fr=0.19$, and f) $Fr=0.17$

Figure 6 shows the variations of the dimensionless scour depth (d_{sm}/D) versus dimensionless debris area (A_d/D^2) for debris located near the free flow surface. The dimensionless scouring depth increases with increasing debris blockage for the non-slotted bridge pier tests (Figure 6a). The increase in the maximum scour depth with increasing blockage area can be attributed to the increased flow velocity beneath the debris due to the reduction of the flow passage area. On the other hand, a fraction of the flow passes through the slot opening and weakens the downward flow upstream of the pier for the slotted pier cases (Figure 6b).

The increase in flow velocity beneath the debris is not significant compared to the non-slotted piers and a relatively constant dimensionless scour depth is observed for all of the tests with slotted piers with different A_d/D^2 values.

In contrast, Figure 7 shows the dimensionless scouring depth versus the dimensionless debris area for the cases where the debris is near the channel bed. As shown in Figure 7, the protective effect of the debris itself, which acts as a countermeasure against the impact of erosive flows, is more effective than the protective effect of the slot inside the pier. It should be noted that $A_d/D^2=0$ in Figures 6 and 7 represents the no-debris conditions.

Fig. 7. Variations of the dimensionless scour depth against dimensionless debris area for the tests with debris located near the channel bed, non-slotted pier: a) $Fr=0.22$, b) $Fr=0.19$, and c) $Fr=0.17$, and slotted pier: d) $Fr=0.22$, e) $Fr=0.19$, and f) $Fr=0.17$

Variations of the percentage reduction in the maximum scour depth compared to the slotted pier without the presence of debris R_{S-ND} are shown in Figure 8. R_{S-ND} is computed as:

$$R_{S-ND} = \frac{d_{sm} - d_{S-ND}}{d_{S-ND}} \times 100 \quad (2)$$

where d_{S-ND} denotes the maximum scour depth around the pier in the tests with slotted piers and no-debris conditions.

Fig. 8. Variations of the maximum scour depth in the slotted or debris loaded piers compared to that of the slotted pier without debris

Debris types D1, D2, D3, and D4 located near the water surface increase the maximum scour depth up to 19%, 26%, 83%, and 70% for the slotted pier, and up to 118%, 159%, 150%, and 137% for the standard pier conditions, respectively. The observed results are somewhat different when the debris is located near the bed. While for the non-slotted pier tests, the maximum scour depth increases up to 21%, 190%, and 48% for D1, D3, and D4 debris types located on the bed, it decreases up to 12% for the D2 debris. Also, for the slotted pier with debris located adjacent

to the bed, the slot reduces the maximum scour depth for debris types D1, D2, and D4. However, d_{sm} decreases up to 102% compared to the **slotted debris without**.

Figure 9 shows the dimensionless contour map of the bed scour and the effect of the slot, debris and the debris position on the scour hole for debris D2 and Fr_3 , for half of the channel. The scour hole spreads around the pier and the maximum scour depth upstream of the pier is $1.15D$ for the NS-ND- Fr_3 test (Figure 9a). The scour extends to a distance of about $3D$ downstream of the pier. After the addition of debris D2 under the water surface, i.e. in the NS-D2- Fr_3 test, the scour expansion area upstream of the pier narrows and the upstream slope of the scour hole increases (Figure 9b). The maximum scouring depth increases to $1.275D$. After adding the slot at the pier model (Figure 9c), the maximum scour depth significantly reduces to $0.9D$. The presence of a slot, in addition to reducing the scour depth compared to the no-slot mode, also significantly reduces the slope of the scour hole. Changing the position of the debris from the water surface to near the bed surface has led to a general deformation of the scour hole compared to other tests (Figure 9d). Accordingly, the maximum scour depth reduces to $0.525D$. Also, the development of scour holes is weakened upstream of the pier and stopped downstream, which can be due to the effect of debris on the flow structure and the weakening of the downflow and subsequently, the weakening of the horseshoe vortex and wake vortex downstream of the pier. This finding is in agreement with results obtained by Ebrahimi et al. (2018), Müller et al. (2001), Vijayasree et al. (2019).

Fig. 9. Contour plots of scour depth around the pier in different tests, a) NS-ND- Fr_3 , b) NS-D2- Fr_3 , c) S-D2- Fr_3 , and d) S-D2- Fr_3 -Bed

Figure 10 shows the contour maps of the dimensionless scour depth for D3 and D4 debris types in two positions near the water surface and adjacent to the bed. The accumulation of debris

near the bed leads to a reduction in the maximum scouring depth as well as a reduction in the scouring area around the pier. The combination of slot and debris reduces the erosion around the pier for the S-D4- Fr_3 -Bed test. It shrinks the main scour hole near the pier and a secondary scour hole forms relatively far downstream from the pier that will not have much impact on the stability of the bridge structure. It should be noted that the secondary scour hole downstream of the pier in the presence of debris installed at the initial bed elevation was not observed by Ebrahimi et al. (2018) for masonry bridges with piers with a large length to diameter ratio.

Fig. 10. Contour plots of scour depth around the pier in different tests, a) S-D3- Fr_3 , b) S-D3- Fr_3 -Bed, c) S-D4- Fr_3 , and d) S-D4- Fr_3 -Bed

Table 2 shows a comparison of the results obtained in the present study with data available in the literature with particular reference to the effect of slot and debris on the changes of maximum scour depth. The studies used in this table are the closest in terms of piers, flows, and slots dimensions to the present study. Accordingly, Chiew (1992), Kumar et al., (1999), and Grimaldi et al., (2009b) reported a 9%, 19%, and 30% reduction in the maximum scour depth, respectively, due to the slot in the pier. However, the results of the present study showed that although the slot in the pier alone leads to a 39% reduction in the maximum scour depth, the presence of debris can lead to a decrease or increase in the maximum scour depth compared to a standard pier without debris depending on the debris location. Accordingly, if the debris is located near the water surface, the maximum scouring depth can be reduced up to 32% or increased up to 11%, depending on the shape of the accumulated materials. In contrast, if objects accumulate near the bed, the maximum scour depth may decrease up to 55% or increase up to 23% depending on the shape of the accumulated material. The maximum percentage increase in the d_{sm} was reported by [89] for the debris loaded pier. It should be noted that different shapes and sizes of debris produce different

scour depths. As a consequence, the results presented in the present paper are limited to the tested range of debris characteristics.

Table 2. Effects of slot and debris on the variations of the maximum scour depth^{*}

Conclusion

Many rivers normally carry materials such as leaves, branches, roots and tree trunks, a phenomenon naturally observed with the decay of riparian vegetation. Accumulation of these materials in the vicinity of hydraulic structures such as bridge piers can lead to problems in their proper operation. In this study, the effect of debris accumulated upstream of a slotted cylindrical bridge pier model was investigated experimentally. Four debris models were investigated under three different flow conditions. The results showed that, although the slot alone could reduce the maximum scour depth around the pier by up to 39%, the presence of debris could affect its performance. The maximum scouring depth around the pier decreased compared to the no-debris conditions for some shapes of debris and increased for others, indicating that the accumulation of floating objects can have a significant effect on the stability of the bridge structure. The position of debris accumulation also affects the performance of the slot and the geometry of the scour hole. In general, debris near the bed can lead to a reduction of scouring as a result of the sheltering effect. This sheltering can be different depending on the shape of the accumulation of the debris upstream of the pier. It can be concluded that the accumulation of debris upstream of the pier has an important effect on the performance of the slot in the protection of the pier against scour and it is necessary to be careful in rivers that carry large quantities of debris. Further research with different

flows, sediments, bridge piers, slots and debris conditions is needed to provide a general guide to slot operation in the presence of debris for use in hydraulic and structural bridge pier design.

References

1. Wardhana K, Hadipriono FC (2003) Analysis of Recent Bridge Failures in the United States. *J Perform Constr Facil* 17:144–150
2. Scozzese F, Ragni L, Tubaldi E, Gara F (2019) Modal properties variation and collapse assessment of masonry arch bridges under scour action. *Eng Struct* 199:109665. <https://doi.org/10.1016/j.engstruct.2019.109665>
3. Guo X, Zhang C, Chen ZQ (2020) Dynamic performance and damage evaluation of a scoured double-pylon cable-stayed bridge under ship impact. *Eng Struct* 216:110772. <https://doi.org/10.1016/j.engstruct.2020.110772>
4. Tubaldi E, Macorini L, Izzuddin BA, et al (2017) A framework for probabilistic assessment of clear-water scour around bridge piers. *Struct Saf* 69:11–22. <https://doi.org/10.1016/j.strusafe.2017.07.001>
5. Pizarro A, Manfreda S, Tubaldi E (2020) The Science behind Scour at Bridge Foundations: A Review. *Water* 12:374. <https://doi.org/10.3390/W12020374>
6. Carnacina I, Pagliara S, Leonardi N (2019) Bridge pier scour under pressure flow conditions. *River Res Appl* 35:844–854. <https://doi.org/10.1002/rra.3451>
7. Melville BW, Chiew Y-MM (1999) Time Scale for Local Scour at Bridge Piers. *J Hydraul Eng* 125:59–65. [https://doi.org/10.1061/\(ASCE\)0733-9429\(1999\)125:1\(59\)](https://doi.org/10.1061/(ASCE)0733-9429(1999)125:1(59))
8. Lin C, Bennett C, Han J, Parsons RL (2012) Integrated analysis of the performance of pile-supported bridges under scoured conditions. *Eng Struct* 36:27–38. <https://doi.org/10.1016/j.engstruct.2011.11.015>
9. Pandey M, Oliveto G, Pu JH, et al (2020) Pier scour prediction in non-uniform gravel beds. *Water (Switzerland)* 12:1696. <https://doi.org/10.3390/W12061696>
10. Chiew YM (1995) Mechanics of riprap failure at bridge piers. *J Hydraul Eng* 121:635–643. [https://doi.org/10.1061/\(ASCE\)0733-9429\(1995\)121:9\(635\)](https://doi.org/10.1061/(ASCE)0733-9429(1995)121:9(635))
11. Chiew YM (2004) Local Scour and Riprap Stability at Bridge Piers in a Degrading Channel. *J Hydraul Eng* 130:218–226. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2004\)130:3\(218\)](https://doi.org/10.1061/(ASCE)0733-9429(2004)130:3(218))
12. Chiew YM, Lim F-H (2000) Failure behavior of riprap layer at bridge piers under live-bed conditions. *J Hydraul Eng* 126:43–55. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2000\)126:1\(43\)](https://doi.org/10.1061/(ASCE)0733-9429(2000)126:1(43))
13. Lauchlan CS, Melville BW (2001) Riprap Protection at Bridge Piers. *J Hydraul Eng* 127:412–418. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2001\)127:5\(412\)](https://doi.org/10.1061/(ASCE)0733-9429(2001)127:5(412))
14. Froehlich DC (2013) Protecting bridge piers with loose rock riprap. *J Appl Water Eng Res* 1:39–57. <https://doi.org/10.1080/23249676.2013.828486>

15. Unger J, Hager WH (2006) Riprap Failure at Circular Bridge Piers. *J Hydraul Eng* 132:354–362. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2006\)132:4\(354\)](https://doi.org/10.1061/(ASCE)0733-9429(2006)132:4(354))
16. Korkut R, Martinez EJ, Morales R, et al (2007) Geobag performance as scour countermeasure for bridge abutments. *J Hydraul Eng* 133:431–439. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2007\)133:4\(431\)](https://doi.org/10.1061/(ASCE)0733-9429(2007)133:4(431))
17. Akib S, Liana Mamat N, Basser H, Jahangirzadeh A (2014) Reducing local scouring at bridge piles using collars and geobags. *Sci World J* 2014:1–7. <https://doi.org/10.1155/2014/128635>
18. Pagliara S, Carnacina I, Cigni F (2010) Sills and gabions as countermeasures at bridge pier in presence of debris accumulations. *J Hydraul Res* 48:764–774. <https://doi.org/10.1080/00221686.2010.528184>
19. Yoon TH, Kim D-H (2001) Bridge Pier Scour Protection by Sack Gabions. In: *Bridging the Gap*. American Society of Civil Engineers, Reston, VA, pp 1–8
20. Tang HW, Ding B, Chiew YM, Fang SL (2009) Protection of bridge piers against scouring with tetrahedral frames. *Int J Sediment Res* 24:385–399. [https://doi.org/10.1016/S1001-6279\(10\)60012-1](https://doi.org/10.1016/S1001-6279(10)60012-1)
21. Zarrati AR, Gholami H, Mashahir MB (2004) Application of collar to control scouring around rectangular bridge piers. *J Hydraul Res* 42:97–103. <https://doi.org/10.1080/00221686.2004.9641188>
22. Masjedi A, Bejestan MS, Esfandi A (2010) Reduction of local scour at a bridge pier fitted with a collar in a 180 degree flume bend (Case study: oblong pier). *J Hydrodyn Ser B* 22:669–673. [https://doi.org/10.1016/S1001-6058\(10\)60012-1](https://doi.org/10.1016/S1001-6058(10)60012-1)
23. Heidarpour M, Afzalimehr H, Izadinia E (2010) Reduction of local scour around bridge pier groups using collars. *Int J Sediment Res* 25:411–422. [https://doi.org/10.1016/S1001-6279\(11\)60008-5](https://doi.org/10.1016/S1001-6279(11)60008-5)
24. Bestawy A, Eltahawy T, Alsaluli A, et al (2020) Reduction of local scour around a bridge pier by using different shapes of pier slots and collars. *Water Sci Technol Water Supply* 20:1006–1015. <https://doi.org/10.2166/ws.2020.022>
25. Memar S, Zounemat-Kermani M, Beheshti A, et al (2020) Influence of collars on reduction in scour depth at two piers in a tandem configuration. *Acta Geophys* 68:229–242. <https://doi.org/10.1007/s11600-019-00393-0>
26. Hamidifar H, Shahabi-Haghighi SMB, Chiew YM (2021) Collar performance in bridge pier scour with debris accumulation. *Int J Sediment Res*. <https://doi.org/10.1016/J.IJSRC.2021.10.002>
27. Dey S, Sumer BM, Fredsøe J (2006) Control of Scour at Vertical Circular Piles under Waves and Current. *J Hydraul Eng* 132:270–279. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2006\)132:3\(270\)](https://doi.org/10.1061/(ASCE)0733-9429(2006)132:3(270))
28. Tafarojnoruz A, Gaudio R, Calomino F (2012) Evaluation of flow-altering countermeasures against bridge pier scour. *J Hydraul Eng* 138:297–305. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0000512](https://doi.org/10.1061/(ASCE)HY.1943-7900.0000512)

- 497 29. Chiew YM, Lim S (2003) Protection of bridge piers using a sacrificial sill. *Proc Inst Civ*
498 *Eng - Water Marit Eng* 156:53–62. <https://doi.org/10.1680/wame.2003.156.1.53>
- 499 30. Grimaldi C, Gaudio R, Calomino F, Cardoso AH (2009) Countermeasures against local
500 scouring at bridge piers: slot and combined system of slot and bed sill. *J Hydraul Eng*
501 135:425–431. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0000035](https://doi.org/10.1061/(ASCE)HY.1943-7900.0000035)
- 502 31. Hamidifar H, Omid MH, Nasrabadi M (2018) Reduction of scour using a combination of
503 riprap and bed sill. 171:264–270. <https://doi.org/10.1680/jwama.16.00073>
- 504 32. Hamidifar H, Nasrabadi M, Omid MH (2018) Using a bed sill as a scour countermeasure
505 downstream of an apron. *Ain Shams Eng J* 9:1663–1669.
506 <https://doi.org/10.1016/j.asej.2016.08.016>
- 507 33. Ghorbani B, Kells JA (2008) Effect of submerged vanes on the scour occurring at a
508 cylindrical pier. *J Hydraul Res* 46:610–619. <https://doi.org/10.3826/jhr.2008.3003>
- 509 34. Zarei E, Vaghefi M, Hashemi SS (2019) Bed topography variations in bend by
510 simultaneous installation of submerged vanes and single bridge pier. *Arab J Geosci* 12:1–
511 10. <https://doi.org/10.1007/s12517-019-4342-z>
- 512 35. Khaple S, Hanmaiahgari PR, Gaudio R, Dey S (2017) Splitter plate as a flow-altering pier
513 scour countermeasure. *Acta Geophys* 65:957–975. <https://doi.org/10.1007/s11600-017-0084-z>
514
- 515 36. Melville BW, Hadfield AC (1999) Use of Sacrificial Piles as Pier Scour Countermeasures.
516 *J Hydraul Eng* 125:1221–1224. [https://doi.org/10.1061/\(ASCE\)0733-9429\(1999\)125:11\(1221\)](https://doi.org/10.1061/(ASCE)0733-9429(1999)125:11(1221))
517
- 518 37. Park JH, Sok C, Park CK, Kim Y Do (2016) A study on the effects of debris accumulation
519 at sacrificial piles on bridge pier scour: I. Experimental results. *KSCE J Civ Eng* 20:1546–
520 1551. <https://doi.org/10.1007/s12205-015-0207-5>
- 521 38. Chiew YM (1992) Scour protection at bridge piers. *J Hydraul Eng* 118:1260–1269.
522 [https://doi.org/10.1061/\(ASCE\)0733-9429\(1992\)118:9\(1260\)](https://doi.org/10.1061/(ASCE)0733-9429(1992)118:9(1260))
- 523 39. Kumar V, Raju KGR, Vittal N (1999) Reduction of Local Scour around Bridge Piers
524 Using Slots and Collars. *J Hydraul Eng* 125:1302–1305.
525 [https://doi.org/10.1061/\(ASCE\)0733-9429\(1999\)125:12\(1302\)](https://doi.org/10.1061/(ASCE)0733-9429(1999)125:12(1302))
- 526 40. Hajikandi H, Golnabi M (2018) Y-shaped and T-shaped slots in river bridge piers as scour
527 countermeasures. *Proc Inst Civ Eng - Water Manag* 171:253–263.
528 <https://doi.org/10.1680/jwama.16.00063>
- 529 41. Obied N, Khassaf S (2019) Experimental Study for Protection of Piers Against Local
530 Scour Using Slots. *Int J Eng* 32:217–222
- 531 42. Hosseini SA, Osroush M, Kamanbedast AA, Khosrojerrdi A (2020) The effect of slot
532 dimensions and its vertical and horizontal position on the scour around bridge abutments
533 with vertical walls. *Sadhana - Acad Proc Eng Sci* 45:1–16.
534 <https://doi.org/10.1007/s12046-020-01343-z>
- 535 43. Osrush M, Hosseini SA, Kamanbedast AA (2020) Evaluation and comparison of the slots
536 and collars performance in reducing scouring around bridge abutments. *Amirkabir J Civ*

Eng 52:1637–1650. <https://doi.org/10.22060/ceej.2019.15565.5953>

44. Sharma S (1999) Effect of Slot on Scour around a Pier. Kurukshetra University
45. Heidarpour M (2002) Control and reduction of local scour at bridge piers by using slot. In: Bousmar D, Zech Y (eds) *River Flow: Proceedings of the International Conference on Fluvial Hydraulics*. IAHR, Louvain-la-Neuve, Belgium, pp 1069–1072
46. Grimaldi C, Gaudio R, Calomino F, Cardoso AH (2009) Control of Scour at Bridge Piers by a Downstream Bed Sill. *J Hydraul Eng* 135:13–21. [https://doi.org/10.1061/\(ASCE\)0733-9429\(2009\)135:1\(13\)](https://doi.org/10.1061/(ASCE)0733-9429(2009)135:1(13))
47. Tanaka S, Yano M (1967) Local scour around a circular cylinder. In: *Twelfth Congress of the International Association for Hydraulic Research*. pp 193–201
48. Azevedo M, Leite F, Lima M (2014) Experimental study of scour around circular and elongated bridge piers with and without pier slot. In: Avilez-Valente P, Carvalho E, Silva Lopes A (eds) *MEFTE 2014*. Porto, Portugal, pp 195–200
49. Gaudio R, Tafarojnoruz A, Calomino F (2012) Combined flow-altering countermeasures against bridge pier scour. *J Hydraul Res* 50:35–43. <https://doi.org/10.1080/00221686.2011.649548>
50. Moncada-M AT, Aguirre-Pe J, Bolívar JC, Flores EJ (2009) Scour protection of circular bridge piers with collars and slots. *J Hydraul Res* 47:119–126. <https://doi.org/10.3826/jhr.2009.3244>
51. Panici D, de Almeida GAM (2018) Formation, Growth, and Failure of Debris Jams at Bridge Piers. *Water Resour Res* 54:6226–6241. <https://doi.org/10.1029/2017WR022177>
52. Schalko I, Lageder C, Schmocker L, et al (2019) Laboratory Flume Experiments on the Formation of Spanwise Large Wood Accumulations: Part II-Effect on local scour. *Water Resour Res* 55:4871–4885. <https://doi.org/10.1029/2019WR024789>
53. Dixon SJ, Sear DA (2014) The influence of geomorphology on large wood dynamics in a low gradient headwater stream. *Water Resour Res* 50:9194–9210. <https://doi.org/10.1002/2014WR015947>
54. Cantero-Chinchilla FN, Almeida GAM de, Manes C (2021) Temporal Evolution of Clear-Water Local Scour at Bridge Piers with Flow-Dependent Debris Accumulations. *J Hydraul Eng* 147:06021013. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0001920](https://doi.org/10.1061/(ASCE)HY.1943-7900.0001920)
55. Panici D, Kripakaran P (2021) Trapping Large Wood Debris in Rivers: Experimental Study of Novel Debris Retention System. *J Hydraul Eng* 147:04020101. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0001859](https://doi.org/10.1061/(ASCE)HY.1943-7900.0001859)
56. Wohl E, Kramer N, Ruiz-Villanueva V, et al (2019) The Natural Wood Regime in Rivers. *Bioscience* 69:259–273. <https://doi.org/10.1093/BIOSCI/BIZ013>
57. Schmocker L, Weitbrecht V (2013) Driftwood: Risk Analysis and Engineering Measures. *J Hydraul Eng* 139:683–695. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0000728](https://doi.org/10.1061/(ASCE)HY.1943-7900.0000728)
58. Schmocker L, Hager WH (2013) Scale modeling of wooden debris accumulation at a debris rack. *J Hydraul Eng* 139:827–836. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0000714](https://doi.org/10.1061/(ASCE)HY.1943-7900.0000714)

- 577 59. Diehl TH (1997) Potential drift accumulation at bridges. US Department of
578 Transportation, Federal Highway Administration Research and Development, McLean,
579 Virginia, USA.
- 580 60. Jamei M, Ahmadianfar I (2020) Prediction of scour depth at piers with debris
581 accumulation effects using linear genetic programming. *Mar Georesources Geotechnol*
582 38:468–479. <https://doi.org/10.1080/1064119X.2019.1595793>
- 583 61. Melville BW, Dongol DM (1992) Bridge pier scour with debris accumulation. *J Hydraul*
584 *Eng* 118:1306–1310. [https://doi.org/10.1061/\(ASCE\)0733-9429\(1992\)118:9\(1306\)](https://doi.org/10.1061/(ASCE)0733-9429(1992)118:9(1306))
- 585 62. Pagliara S, Carnacina I (2013) Bridge pier flow field in the presence of debris
586 accumulation. *Proc Inst Civ Eng - Water Manag* 166:187–198.
587 <https://doi.org/10.1680/wama.11.00060>
- 588 63. Pagliara S, Carnacina I (2011) Influence of wood debris accumulation on bridge pier
589 scour. *J Hydraul Eng* 137:254–261. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0000289](https://doi.org/10.1061/(ASCE)HY.1943-7900.0000289)
- 591 64. Lagasse PF, Zevenbergen LW, Clopper PE (2010) Impacts of debris on bridge pier scour.
592 In: *Scour and Erosion*. American Society of Civil Engineers, Reston, VA, pp 854–863
- 593 65. Benn J (2013) Railway bridge failure during flooding in the UK and Ireland. *Proc Inst Civ*
594 *Eng -Forensic Eng* 166:163–170.
595 <https://doi.org/10.1680/feng.2013.166.4.163>
- 596 66. De Ciccio PN, Paris E, Solari L, Ruiz-Villanueva V (2020) Bridge pier shape influence on
597 wood accumulation: Outcomes from flume experiments and numerical modelling. *J Flood*
598 *Risk Manag* 13:e12599. <https://doi.org/10.1111/jfr3.12599>
- 599 67. Mueller DS, Parola AC (1998) Detailed scour measurements around a debris
600 accumulation. In: *International Water Resources Engineering Conference*. ASCE,
601 Memphis, TN, USA, pp 234–239
- 602 68. Melville BW, Coleman SE (2000) *Bridge Scour*. Water Resources Publication.
- 603 69. Ruiz-Villanueva V, Piégay H, Gurnell AA, et al (2016) Recent advances quantifying the
604 large wood dynamics in river basins: New methods and remaining challenges. *Rev*
605 *Geophys* 54:611–652. <https://doi.org/10.1002/2015RG000514>
- 606 70. Rahimi E, Qaderi K, Rahimpour M, et al (2020) Scour at side by side pier and abutment
607 with debris accumulation. *Mar Georesources Geotechnol* 1–12.
608 <https://doi.org/10.1080/1064119x.2020.1716122>
- 609 71. Rahimi E, Qaderi K, Rahimpour M, Ahmadi MM (2018) Effect of debris on piers group
610 scour: an experimental study. *KSCE J Civ Eng* 22:1496–1505.
611 <https://doi.org/10.1007/s12205-017-2002-y>
- 612 72. Briaud JL, Chen HC, Chang KA, et al (2006) Scour at bridges due to debris
613 Accumulation: A Review. In: *3rd International Conference on Scour and Erosion (ICSE-*
614 *3)*. Amsterdam, The Netherlands, pp 113–120
- 615 73. Lyn DA, Cooper TJ, Condon CA, Gan L (2007) Factors in debris accumulation at bridge
616 piers. Purdue University, West Lafayette, Indiana

74. Ebrahimi M, Kripakaran P, Prodanović DM, et al (2018) Experimental study on scour at a sharp-nose bridge pier with debris blockage. *J Hydraul Eng* 144:04018071. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0001516](https://doi.org/10.1061/(ASCE)HY.1943-7900.0001516)
75. Dias AJ, Fael CS, Núñez-González F (2019) Effect of Debris on the Local Scour at Bridge Piers. In: *IOP Conf. Series: Materials Science and Engineering*. pp 1–10
76. Tafarojnoruz A, Gaudio R (2011) Sills and gabions as countermeasures at bridge pier in the presence of debris accumulations. *J. Hydraul. Res.* 49:832–833
77. Chiew YM, Melville BW (1987) Local scour around bridge piers. *J Hydraul Res* 25:15–26. <https://doi.org/10.1080/00221688709499285>
78. Lee SO, Sturm TW (2009) Effect of Sediment Size Scaling on Physical Modeling of Bridge Pier Scour. *J Hydraul Eng* 135:793–802. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0000091](https://doi.org/10.1061/(ASCE)HY.1943-7900.0000091)
79. Ebrahimi M, Kahraman M, Kripakaran R; (2017) Scour and hydrodynamic effects of debris blockage at masonry bridges: insights from experimental and numerical modelling A NOTE ON VERSIONS. *International Association for Hydro-Environment Engineering and Research (IAHR)*
80. Panici D, de Almeida GAM (2020) Influence of pier geometry and debris characteristics on wood debris accumulations at bridge piers. *J Hydraul Eng* 146:04020041. [https://doi.org/10.1061/\(ASCE\)HY.1943-7900.0001757](https://doi.org/10.1061/(ASCE)HY.1943-7900.0001757)
81. Beechie TJ, Sibley TH (1997) Relationships between Channel Characteristics, Woody Debris, and Fish Habitat in Northwestern Washington Streams. *Trans Am Fish Soc* 126:217–229. [https://doi.org/10.1577/1548-8659\(1997\)126<0217:rbccwd>2.3.co;2](https://doi.org/10.1577/1548-8659(1997)126<0217:rbccwd>2.3.co;2)
82. Kail J (2003) Influence of large woody debris on the morphology of six central European streams. *Geomorphology* 51:207–223. [https://doi.org/10.1016/S0169-555X\(02\)00337-9](https://doi.org/10.1016/S0169-555X(02)00337-9)
83. Comiti F, Andreoli A, Lenzi MA, Mao L (2006) Spatial density and characteristics of woody debris in five mountain rivers of the Dolomites (Italian Alps). *Geomorphology* 78:44–63. <https://doi.org/10.1016/j.geomorph.2006.01.021>
84. Magilligan FJ, Nislow KH, Fisher GB, et al (2008) The geomorphic function and characteristics of large woody debris in low gradient rivers, coastal Maine, USA. *Geomorphology* 97:467–482. <https://doi.org/10.1016/j.geomorph.2007.08.016>
85. Hamidifar H, Zanganeh-Inaloo F, Carnacina I (2021) Hybrid scour depth prediction equations for reliable design of bridge piers. *Water* 2021, Vol 13, Page 2019 13:2019. <https://doi.org/10.3390/W13152019>
86. Ebrahimi M, Djordjević S, Panici D, et al (2020) A method for evaluating local scour depth at bridge piers due to debris accumulation. *Proc Inst Civ Eng Bridg Eng* 173:86–99. <https://doi.org/10.1680/jbren.19.00045>
87. Müller G, Mach R, Kauppert K (2001) Mapping of bridge pier scour with projection moiré. *J Hydraul Res* 39:531–537. <https://doi.org/10.1080/00221686.2001.9628277>
88. Vijayasree BA, Eldho TI, Mazumder BS, Ahmad N (2019) Influence of bridge pier shape on flow field and scour geometry. *Int J River Basin Manag* 17:109–129.

<https://doi.org/10.1080/15715124.2017.1394315>

89. Cantero-Chinchilla FN, de Almeida GAM, Escameia M (2018) Assessing the effects of debris accumulations at river bridges. Southampton, UK
90. Pasokhi-Dargah Z, Esmaeili-Varaki M, Shafee-Sabet B (2018) Study of Local Scour around Vertical Bridge Pier Groups in Presence of Debris Accumulation. Irrig Drain Struct Eng Res 18:1–16

Table 1. Summary of the experimental conditions

Test code	Q (lit/s)	H (mm)	D (mm)	b (mm)	U/U_c (-)	Fr (-)	L_x (mm)	L_y (mm)	L_z (mm)
NS-ND-130	12.9	130	40	10	0.83	0.220	-	-	-
NS-ND-160	15.3	160	40	10	0.80	0.191	-	-	-
NS-ND-180	16.7	180	40	10	0.77	0.175	-	-	-
S-ND-130	12.9	130	40	10	0.83	0.220	-	-	-
S-ND-160	15.3	160	40	10	0.80	0.191	-	-	-
S-ND-180	16.7	180	40	10	0.77	0.175	-	-	-
S-D1-130	12.9	130	40	10	0.83	0.220	12	200	12
S-D2-130	12.9	130	40	10	0.83	0.220	24	200	24
S-D3-130	12.9	130	40	10	0.83	0.220	24	200	24
S-D4-130	12.9	130	40	10	0.83	0.220	100	200	12
S-D1-160	15.3	160	40	10	0.80	0.191	12	200	12
S-D2-160	15.3	160	40	10	0.80	0.191	24	200	24
S-D3-160	15.3	160	40	10	0.80	0.191	24	200	24
S-D4-160	15.3	160	40	10	0.80	0.191	100	200	12
S-D1-180	16.7	180	40	10	0.77	0.175	12	200	12
S-D2-180	16.7	180	40	10	0.77	0.175	24	200	24
S-D3-180	16.7	180	40	10	0.77	0.175	24	200	24
S-D4-180	16.7	180	40	10	0.77	0.175	100	200	12
NS-D1-130	12.9	130	40	10	0.83	0.220	12	200	12
NS-D1-160	15.3	160	40	10	0.80	0.191	12	200	12
NS-D1-180	16.7	180	40	10	0.77	0.175	12	200	12
NS-D2-130	12.9	130	40	10	0.83	0.220	24	200	24
NS-D2-160	15.3	160	40	10	0.80	0.191	24	200	24
NS-D2-180	16.7	180	40	10	0.77	0.175	24	200	24
NS-D3-130	12.9	130	40	10	0.83	0.220	24	200	24
NS-D3-160	15.3	160	40	10	0.80	0.191	24	200	24
NS-D3-180	16.7	180	40	10	0.77	0.175	24	200	24
NS-D4-130	12.9	130	40	10	0.83	0.220	100	200	12
NS-D4-160	15.3	160	40	10	0.80	0.191	100	200	12
NS-D4-180	16.7	180	40	10	0.77	0.175	100	200	12
NS-D1-130-Bed	12.9	130	40	10	0.83	0.220	12	200	12

NS-D2-130-Bed	12.9	130	40	10	0.83	0.220	24	200	24
NS-D3-130-Bed	12.9	130	40	10	0.83	0.220	24	200	24
NS-D4-130-Bed	12.9	130	40	10	0.83	0.220	100	200	12
S-D1-130-Bed	12.9	130	40	10	0.83	0.220	12	200	12
S-D2-130-Bed	12.9	130	40	10	0.83	0.220	24	200	24
S-D3-130-Bed	12.9	130	40	10	0.83	0.220	24	200	24
S-D4-130-Bed	12.9	130	40	10	0.83	0.220	100	200	12
NS-D1-160-Bed	15.3	160	40	10	0.80	0.191	12	200	12
NS-D2-160-Bed	15.3	160	40	10	0.80	0.191	24	200	24
NS-D3-160-Bed	15.3	160	40	10	0.80	0.191	24	200	24
NS-D4-160-Bed	15.3	160	40	10	0.80	0.191	100	200	12
S-D1-160-Bed	15.3	160	40	10	0.80	0.191	12	200	12
S-D2-160-Bed	15.3	160	40	10	0.80	0.191	24	200	24
S-D3-160-Bed	15.3	160	40	10	0.80	0.191	24	200	24
S-D4-160-Bed	15.3	160	40	10	0.80	0.191	100	200	12
NS-D1-180-Bed	16.7	180	40	10	0.77	0.175	12	200	12
NS-D2-180-Bed	16.7	180	40	10	0.77	0.175	24	200	24
NS-D3-180-Bed	16.7	180	40	10	0.77	0.175	24	200	24
NS-D4-180-Bed	16.7	180	40	10	0.77	0.175	100	200	12
S-D1-180-Bed	16.7	180	40	10	0.77	0.175	12	200	12
S-D2-180-Bed	16.7	180	40	10	0.77	0.175	24	200	24
S-D3-180-Bed	16.7	180	40	10	0.77	0.175	24	200	24
S-D4-180-Bed	16.7	180	40	10	0.77	0.175	100	200	12

665

666

667

668

669

670

671

672

673

674

675

676

677

Table 2. Effects of slot and debris on the variations of the maximum scour depth^{*}

Reference	Slot location	Debris	Maximum change in d_{sm} (%)
Chiew (1992)	NB	ND	-20
Chiew (1992)	NW	ND	-30
Kumar et al. (1999)	FD	ND	-30
Heidarpour (2002)	NW	ND	-18
Grimaldi et al. (2009b)	FD	ND	-30
Melville and Dongol (1992)	NS	NW	+49
Pagliara and Carnacina (2011)	NS	NW	+195
Pasokhi-Dargah et al. (2018)	NS	NW	+42
Ebrahimi et al. (2018)	NS	NW	+33
Ebrahimi et al. (2018)	NS	NB	-12 to +7
Cantero-Chinchilla et al. (2018)	NS	NW	+75
present study	FD	ND	-39
present study	FD	NW	-32 to +11
present study	FD	NB	-55 to +23

^{*}NB: near the bed, NW: near the water surface, FD: full depth, NS: no-slot, ND: no debris,

Figure legends

Fig. 1. a) schematic view of the experimental flume (Not to scale), b) slot and debris position, c) a photo of the pier and debris located on the bed, and d) different debris types used in the experiments

Fig. 2. Variations of the dimensionless maximum scour depth for slotted and non-slotted piers and different debris conditions ($Fr=0.22$)

Fig. 3. Variations of the dimensionless maximum scour depth (d_{sm}/D) against Froude number (Fr) in different tests: a) ND, b) D1, c) D2, d) D3, e) D4, f) D1-Bed, g) D2-Bed, h) D3-Bed, and i) D4-Bed.

Fig. 4. Variations of the maximum scour depth in the slotted or debris loaded piers compared to that of the control test

Fig. 5. Schematic view of flow around different debris types at different positions: a) cylindrical, b) inverse pyramid, c) rectangular debris located just below the free water surface, d) cylindrical, e) inverse pyramid, and f) rectangular debris located above the bed (Note: the velocity vectors shown in the figure are hypothesised and not observed)

Fig. 6. Variations of the dimensionless scour depth against dimensionless debris area for the tests with debris located near the water surface, non-slotted pier: a) $Fr=0.22$, b) $Fr=0.19$, and c) $Fr=0.17$, and slotted pier: d) $Fr=0.22$, e) $Fr=0.19$, and f) $Fr=0.17$

Fig. 7. Variations of the dimensionless scour depth against dimensionless debris area for the tests with debris located near the channel bed, non-slotted pier: a) $Fr=0.22$, b) $Fr=0.19$, and c) $Fr=0.17$, and slotted pier: d) $Fr=0.22$, e) $Fr=0.19$, and f) $Fr=0.17$

Fig. 8. Variations of the maximum scour depth in the slotted or debris loaded piers compared to that of the slotted pier without debris

Fig. 9. Contour plots of scour depth around the pier in different tests, a) NS-ND- Fr_3 , b) NS-D2- Fr_3 , c) S-D2- Fr_3 , and d) S-D2- Fr_3 -Bed

Fig. 10. Contour plots of scour depth around the pier in different tests, a) S-D3- Fr_3 , b) S-D3- Fr_3 -Bed, c) S-D4- Fr_3 , and d) S-D4- Fr_3 -Bed